

## Geberit WC flush control with electronic flush actuation, battery operation, dual flush, for RF-controlled button



Example image

### Application purposes

- For manual remote flush actuation of Sigma concealed cisterns 12 cm using Geberit RF-controlled button
- For releasing a single or dual flush
- For solid and drywall construction
- Suitable for less-abled installation
- For Sigma concealed cisterns 12 cm
- Not suitable for use with Geberit inserts for in-cistern block

### Characteristics

- Flush actuation via Geberit RF-controlled button, wireless
- Dual flush can be triggered via RF-controlled button
- Single or dual flush can be triggered via flush plate
- Can be combined with flush plates Sigma01 to Sigma60 or Geberit cover plates
- Battery-operated
- Batteries in closed battery compartment in the flushing cistern
- With push-fit connection with cross-polarity protection
- Interval flush preset
- Adjustable interval flush
- Device settings and operation with mobile device via integrated Bluetooth® interface

### Scope of delivery

- Mounting frame with battery compartment, premounted
- Protection plate
- Support block with servomotor and lifting device, premounted

### To order additionally

- Actuator plate or cover plate

- Compatible with Geberit Control App
- Wirelessly connectable with Geberit Gateway via Bluetooth®
- Compatible with Geberit Connect
- Low-noise lifting mechanism
- Electrical lifting device, self-calibrating

### Technical data

Battery type	LR20
Protection degree	IP45
Operating voltage	3 V DC
Power consumption	≤ 4 W
Power consumption standby	0.15 W
Radio frequency	868.4 MHz
Radio frequency distance	10 m
Interval flush, adjustment range	1-168 h
Interval flush, factory setting	24 h
Interval flush time, adjustment range	1-200 s
Interval flush time, factory setting	5 s

- Control electronics with radio receiver
- 2 alkaline manganese batteries LR20, each 1.5 V

- RF-controlled button

Art. no.	Material designation
115.898.00.6	-

### Accessories

- Geberit RF-controlled button for electronic flush actuation