

# Geberit WC flush control with electronic flush actuation, mains operation, dual flush, for RF-controlled button



#### Example image

#### Application purposes

- For manual remote flush actuation of Sigma concealed cisterns 12 cm using Geberit RF-controlled button
- · For releasing a single or dual flush
- For solid and drywall construction
- Suitable for less-abled installation
- · For Sigma concealed cisterns 12 cm
- · Not suitable for use with Geberit inserts for in-cistern block

#### Characteristics

- · Flush actuation via Geberit RF-controlled button, wireless
- Dual flush can be triggered via RF-controlled button
- Single or dual flush can be triggered via flush plate
- Can be combined with Sigma01 to Sigma70 actuator plates or Geberit cover plates
- · Power supply via external power supply unit
- Transformation of mains voltage to extra-low voltage, 12 V DC
- · Operation with extra-low voltage, no mains voltage in cistern
- With push-fit connection with cross-polarity protection
- Interval flush preset
- Adjustable interval flush
- Device settings and operation with mobile device via integrated Bluetooth<sup>®</sup> interface

#### Scope of delivery

· Support block with servomotor and lifting device, premounted

#### To order additionally

- · Actuator plate or cover plate
- RF-controlled button

## Art. no. Material designation

115.897.00.6 -

# Accessories

Geberit RF-controlled button for electronic flush actuation

- Compatible with Geberit Control App
- Wired networkable with Geberit gateway via GEBUS converter
- Wirelessly connectable with Geberit Gateway via Bluetooth<sup>®</sup>
- Compatible with Geberit Connect
- Low-noise lifting mechanism
- Electrical lifting device, self-calibrating

## **Technical data**

Protection degree	IP45
Nominal voltage	85-240 V AC
Mains frequency	50-60 Hz
Operating voltage	12 V DC
Power consumption	≤ 4 W
Power consumption standby	0.15 W
Radio frequency	868.4 MHz
Radio frequency distance	10 m
Interval flush, adjustment range	1-168 h
Interval flush, factory setting	24 h
Interval flush time, adjustment range	1–200 s
Interval flush time, factory setting	5 s

· Control electronics with radio receiver

- Geberit Power & Connect box
- Geberit power supply unit for Power & Connect box